



MEASUREMENTS

Size	10
Ref.	2636
Total length (mm)	280
Entrance glove width (mm)	135
Palm width (mm)	135

GENERAL DESCRIPTION AND MATERIALS

- Welding glove
- **Split cow leather**
- **Split cuff, 15 cm**
- **Kevlar® sewing yarn**
- **Thick lining**
- Colour : blue
- **Split reinforced plam**
- **Superior quality**

SPECIFIC ADVANTAGES

- Comfort
- **Reinforced palm**
- **Very good protection against heat (32s 350 °C ; 17 s 500 °C)**

MAIN APPLICATION FIELDS

- **Welding job**
- Handling of sharp-edged objects
- Heat protection
- Metallurgical industry

PACKAGING

- Packed **by 12**
- **60 pairs** in a box

STANDARDIZATION

This glove is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 5834 Issue 3

EN420:2003+A1:2009
EN 388:1994

Delivered by **Satra (notified body n° 0321)**



3244

- **Abrasion** = 3/4
- **Blade cut** = 2/5
- **Tear** = 4/4
- **Puncture** = 4/4

EN 1149-2

EN12477:2001+A1:2005

Type A

EN 407:1994



434X4X

- Resistance to **flammability** = 4/4
- Resistance to **contact heat** = 3/4
- Resistance to **convective heat** = 4/4
- Resistance to **radiant heat** = X
- Resistance to **small splashes of molden metal** = 4/4
- Resistance to **large splashes of molden metal** = X